



30 Year Warranty Information Sheet

Known for its outstanding performance, durability and colour retention, Timberthane siding is the ultimate choice for homeowners, cottagers, contractors and architects. Timberthane siding is available in any colour of your choice, along with standard and custom profiles to suite your needs and taste.

Follow these instructions to maintain your Timberthane warranty and enjoy the look and benefits of carefree, real wood siding. Timberthane, if installed properly will require little maintenance, nevertheless common sense dictates that installers handle and store Timberthane properly to avoid spoiling or damage.

DO's

Always use colour-matched coating touch-up kit to treat all end cuts. Only coat cut ends, and be sure to avoid getting on exposed face as factory finish is hard to match with brush.

Always use a hammer cap to install colour-matched nails as chipping may occur on heads.

Always treat the siding product with respect. Even though the coating is tough and durable, mishandling can cause unnecessary damage.

Always keep unused touch-up kits away from moisture, excessive heat, and open flames. Ensure lids are firmly closed on the coating and activator containers.

Always caulk edges where butting into trims etc., so water cannot get in behind finished material.

Always use Timberthane coating properly mixed 4:1 with Timberthane activator. Using too much activator will result in a "glossy" finish and uneven cure time. Failure to properly use touch-up will result in a void warranty.

Provide a drainage plane behind siding such as strapping or cedar breather etc.

DONT's

Do not use coating straight from the can for any touch ups, the activator must be used to ensure proper curing.

Do not leave any cuts exposed, use end touch-up on all cuts or substrate will absorb moisture.

Do not over activate coating, use proper mixture to ensure uniform sheen.

Timberthane coating is designed to be factory applied in a controlled environment. Using Timberthane touch-up coating on raw material, or material previously coated in a different product may not yield same look, sheen, or performance. Do not attempt to “touch -up” large areas that may have been damaged. Replace boards as necessary, or call our Timberthane coating department for further instructions.

Do not use varsol or any other consumer ready thinners to reduce coating mixture. Only provided reducer is permitted.

General Information

Touch-up pot life is 3-4 hours when mixed properly, any product left longer has undergone too much air exposure and evaporation, and cannot be re-activated.

Timberthane touch-up is not recommended for use on steel, aluminum, or plastics.

Failure to heed these instructions will result in an improper installation of the Timberthane product line and will void warranty.

Please sign and date below to state you have read and understand the above information. By signing this you agree follow the correct installation procedures as to provide best possible duration of the Timberthane product.

The Timberthane guarantee will only be honoured if installation procedures have been observed in their entirety.

(Signature) (Date)
Company Rep

(Signature) (Date)
Installer/Building Owner





Timberthane Warranty

Muskoka Timber Mills hereby warrants to you, the Owner of the Property named below, that your new Timberthane Pre-finished Wood Siding System is defect-free and that the Timberthane Coating will protect the underlying wood against the elements for as long as you own your Property. Should this not be the case, Muskoka Timber Mills will gladly supply additional coating and, as necessary, will replace any and all siding that has become unsound by virtue of coating failure. During the first five years after the date of sale, we'll also include a Labour Allowance towards the cost of replacing defective coating or siding, as the case may be. The foregoing is subject to proper installation and maintenance, normal wear and tear and to the following terms and coverage limits. Pitch or gum bleeding is considered normal and not a warranty claim.

Terms

This warranty covers functional failures only. Aesthetic factors such as gloss and colour retention, being subjective or site specific, are not covered, nor are abuse, movement and physical damage. Owner is responsible for normal wear and tear, which is deemed to be 3½ % of the total surface area of the project per annum cumulatively. To the extent that the square footage of failure exceeds the above wear and tear allowance, the warranty applies for the full cost of the coating and wood in quantities necessary to replace originally-supplied defective coating or unsound wood. If failure is in the first 1-5 years, the material, coating and labour will be replaced. If failure happens after the 5th year, the material or the coating will be replaced depending on the circumstances. The coverage under this warranty contract is on a one-time basis. Replacement coating and siding carry a five-year warranty against factory defects. This warranty only applies to the wood coated by our staff, in our factory. It does not cover smooth face, only rough. It does not cover hint-o-tint, or shingles and only solid colours. Must have moisture slicker on exterior of building or drainage plane, strapping, etc, to meet building code.



2152 Manitoba Street, Bracebridge, ON P1L 1X4 •
645-7757 www.muskokatimber.com •
timber@muskoka.com

705-